


# HDL-DDLA-3

## DRAWING (mm)



## PHOTO



## MODEL NO. DESIGNATION



Example: HDL-DDLA-1

## OPTIONAL CONTROL BOX AVAILABLE




## GENERAL DATA

Product name	HDL-DDLA-3
Mode	Asynchronous
Number of actuators	3
Compatible control box	DDLA-3
Cable length mm	880   spiral 420
Permissible ambient temperature deg. C	+5°C ~ +40°C
IP	IP20
Connector handset	10P10C (RJ50) Plug
Body material/s	ABS
Color	Pantone cool gray 11C   black   black spiral cable and connector
Color	Black

## CONNECTOR PIN LAYOUT

10P10C (RJ50) Jack



## OPERATION GUIDANCE ASYNCHRONOUS CONTROL BOXES

Press and continuously hold down the M button on the handset for actuator/s operation

The actuator/s will stop at any position when the handset button is released

The actuator/s will stop automatically by its internal limit switches at end position

Simultaneous operation of several actuators is possible

## CONNECTOR PIN CONFIGURATION

10P10C (RJ50)

1	
2	5V
3	3 Up M3
4	2 Up M2
5	1 Up M1
6	3 Down M3
7	2 Down M2
8	1 Down M1
9	
10	